

DRYHILL Mfg

High Volume Liquid Manure Pumps

SUPREME SLURRY PUMP

SUPERIOR PERFORMANCE OUTSTANDING RELIABILITY



DRYHILL Mfg

Suction Pump

The High capacity centrifugal pump transfers manure of a slurry consistency from a reception pit to the storage site. . The Suction Pump provides superior pumping and is designed for mixing and pumping liquid manure in all kinds of applications.

DH528

Features

20" or 28" diameter impeller with 6 blades.
Bearing assembly in oil bath protected by a 3 seal mechanism and a slinger seal to protect seals.
Intake flapper valve with thick rubber to seal against a pipe.
8" intake and 6" or 8" discharge.



Configurations and applications

*The Suction Pump pumping head permitted shown takes into consideration the Pump suction depth. The amount of solids contained in the liquid will progressively reduce the suction depth shown in this chart.

Impeller	Tractor	Usage	Maximun pumping head permitted	Maximun suction depth (Water)
20" (508 mm) dia. X 540 RPM	40 HP min	Pumping water from platforms	* 15 ft (4.5 m)	15 ft (4.5 m)
20" (508 mm) dia. X 1000 RPM	100 HP min	Agitate and pump hog manure	* 15 ft (17 m)	15 ft (4.5 m)
28" (711 mm) dia. X 540 RPM	58 HP min	Agitate and pump hog and cow manure	* 40 ft (12 m)	15 ft (4.5 m)

Visit our website for more information on these Dryhill Mfg. products.
Vertical Pumps * Lagoon Pumps * Suction Pumps * Electric Pumps * Fill Pipes * Hose Reels *
Truck Mount * Slurry Pump * Bale Wagons * Bale Grabbers

Dryhillmfg.com

DRYHILL Mfg



Supreme-Pump and Side Mount Agitator Kit Benefits

Powerful surface and bottom agitation for fast mixing of manure.

A 12" diameter rubber hose is installed between the Supreme-Pump and the reservoir to absorb vibrations.

Note: The Supreme-Pump can be installed above ground level to keep the environment clean and aid in draining the pump once the reservoir is empty



Key Features

Two types of 12" intake pipes available to fit most of the manure reservoirs.

Hydraulic directional valve to select agitation or loading.

12" gate valve with flanges on both ends or with one flange and hose adaptor at the other end.

25 foot or 30 foot load out pipe. Available with low pressure discharge elbow.

180° rotating top agitation nozzle with 120° up and down.

Benefits

Positive agitation to minimize solid residue between the port holes of the pit.

Loading capacity of up to 6000 GPM

Easily transfer to the spreader with the high capacity 8" load pipe.

Hot dipped galvanized coating on agitator and pump.

Key Features

Hydraulic directional valve to select either agitation or loading.

25' or 30' loading pipe. Available with low pressure discharge elbow

Two Knife valves for optimum safety DH530



Straight down Sidewall Agitation Nozzle



Visit our website for more information on these Dryhill Mfg. products.
Vertical Pumps * Lagoon Pumps * Suction Pumps * Electric Pumps * Fill Pipes * Hose Reels *
Truck Mount * Slurry Pump * Bale Wagons * Bale Grabbers

Dryhillmfg.com

DRYHILL Mfg

PROVIDING GREAT PRODUCTS

Vertical Manure Pumps

Adjustable Pit Pumps

Slurry Store Systems

Fill Pipe On Wheels

Stationary PTO Pumps

Lagoon Pumps

Suction Pumps

Propeller Agitation

Electric Transfer Pumps

Boom Kits

Bale Grabbers

Bale Wagons

Hose Reels

Truck Mount Pumps

Custom Products

Tank is 101' x 19'



DRYHILL Mfg

Dryhill Manufacturing LLC
554 N Crossroads Road
Lykens, PA 1704

Authorized Dealer

Visit our website for more information on these Dryhill Mfg. products.
Vertical Pumps * Lagoon Pumps * Suction Pumps * Electric Pumps * Fill Pipes * Hose Reels *
Truck Mount * Slurry Pump * Bale Wagons * Bale Grabbers

Dryhillmfg.com